

# Question Sheet for Computational Robot Dynamics 2022

Instructor: Roy Featherstone, Italian Institute of Technology

Website: <http://royfeatherstone.org/teaching>

© 2022 Roy Featherstone

**Note:** All questions that involve the use of Matlab, but do not require the use of either Simulink or ‘showmotion’ from `spatial_v2`, can be performed equally well on Matlab or GNU Octave.

## Questions for Part 1 — Modelling

### Question Mod1

Write Matlab functions to perform each of the following calculations. In each case, `lam` is a parent array. Avoid using recursion, and avoid algorithms with a worse-than-linear complexity.

- (a) `Ka=kappa(lam)` where `Ka` is a cell array such that `Ka{i}` is  $\kappa(i)$ .
- (b) `Mu=mu(lam)` where `Mu` is a cell array such that `Mu{i+1}` is  $\mu(i)$ , so `Mu{1}` is  $\mu(0)$ .
- (c) `Nu=nu(lam)` where `Nu` is a cell array such that `Nu{i}` is  $\nu(i)$ .
- (d) `d=depth(lam)` where `d` is the depth of the tree, defined as  $d = \max_i |\kappa(i)|$  (where  $|S|$  is the number of elements in set  $S$ ).

### Question Mod2

Following the examples on Slide 16, work out the joint models for each of the following joint types:

- (a) a cylindrical joint on the  $x$  axis;
- (b) a helical joint of pitch  $h$  (in metres per radian) on the  $y$  axis, using the rotation angle as its joint variable;
- (c) a rack-and-pinion joint (i.e., a cylinder rolling without slipping on a plane) in which the parent body is the rack (plane), the child is the pinion (cylinder), the pinion has a radius of  $r$ , the pinion’s rotation axis is parallel to the  $x$  axis, and positive rotation of the pinion causes it to translate in the  $-y$  direction, so the rack is parallel to the  $x$ - $y$  plane and below the pinion. Put the origin of the successor frame at the centre of the pinion.

## Questions for Part 2 — Inverse Dynamics

### Question ID1

Write a function that uses the function `ID` from `Spatial_v2` to calculate the coefficients  $\mathbf{H}$  and  $\mathbf{C}$  of the general joint-space equation of motion

$$\boldsymbol{\tau} = \mathbf{H}\ddot{\mathbf{q}} + \mathbf{C}.$$

Ignore the possibility that there may be external forces. Compare your answers with the values computed by `HandC`.

## Questions for Part 3 — Efficiency

### Question Eff1

Create two robots using `planar(2)`, and modify one of them by adding a point mass to link 2 and a corresponding negative point mass to link 1, as described on slides 13–15. Do they have the same inverse dynamics? (Tip: read the documentation for `mcI`, and remember that `planar` produces models that use planar vectors rather than spatial vectors.)

## Questions for Part 4 — Forward Dynamics (CRBA)

### Question FD1

Enter the following lower-triangular matrix into Matlab:

$$L = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 \\ 2 & 3 & 0 & 0 & 0 \\ 4 & 0 & 5 & 0 & 0 \\ 6 & 0 & 7 & 8 & 0 \\ 9 & 0 & 10 & 0 & 11 \end{bmatrix};$$

- (a) What value of `lambda` goes with this matrix?
- (b) Calculate the matrix  $A=L'*L$ . Does it have the same sparsity pattern?
- (c) Calculate  $L2=LTL(A,lambda)$  using your answers to parts (a) and (b). Is  $L2$  the same as  $L$ ?
- (d) Now try  $L3=LTL(A,[0,1,2,3,4])$ . What do you notice?

## Questions for Part 6 — Simulation




Figure 1




Figure 2

### Question Sim1

Figure 1 shows a cone that is rolling without slipping on the  $x$ - $y$  plane. Its apex is at the origin, and the cone is rolling at a constant speed such that the line of contact makes one rotation around the  $z$  axis per second. At time  $t = 0$  the cone is touching the  $x$  axis; at time  $t = 0.25$  it is touching the  $y$  axis; and at time  $t = 1$  it is again touching the  $x$  axis. The half angle at the cone's apex is  $30^\circ$ , which means that the cone will rotate twice around its own axis for each one rotation of the line of contact about the  $z$  axis.

- (a) Write a Matlab function `w=conew(t)` that calculates the cone's angular velocity as a function of time.
- (b) Write a Matlab function `qd=coneqd(t,q)` to calculate the time derivative of a quaternion,  $q(t)$ , representing the orientation of the cone at time  $t$ , given both  $t$  and  $q(t)$ . This function should use the functions `conew` from your answer to part (a) and `rqd` from `spatial_v2`.

- (c) Issue the Matlab command `[T,Q]=ode45(@coneqd,[0,1],q0);` where  $\mathbf{q}_0=[1;0;0;0]$  is the initial value of  $\mathbf{q}$  (i.e.,  $\mathbf{q}(0)$ ). This function will integrate the motion of the cone for one second. Plot the result using `plot(T,Q)`. Do you understand the resulting graph? Is it correct? **Tip:** you can force the integrator to take smaller steps, to get a smoother-looking graph, with an optional extra argument to `ode45` of the form `odeset('MaxStep',0.01)`.

Note: Matlab normally updates its internal copy of a user-defined function each time it is called from the command line; but it does not do so if the function is called via its handle, as in `@coneqd`. Therefore, each time you modify `coneqd` while working on part (c), you will have to call it explicitly at least once to make Matlab update its internal copy.

### Question Sim2

Figure 2 shows a situation identical to the one in Figure 1 except that the cone is translated one metre in the  $y$  direction so that its apex is at the point  $(0, 1, 0)$ . All other aspects of the motion are the same as in question 1.

- Write a Matlab function `v=conev(t)` that calculates the cone's spatial velocity as a function of time.
- Write a Matlab function `pd=conepd(t,p)` to calculate the time derivative of a 7-element position coordinate vector  $\mathbf{p}(t) = [\mathbf{q}(t)^T \mathbf{r}(t)^T]^T$ , in which  $\mathbf{q}(t)$  is a quaternion representing the orientation of the cone at time  $t$ , as in question 1, and  $\mathbf{r}(t)$  is a vector giving the position of the body-fixed point on the cone that coincides with the origin (not the apex) at time  $t = 0$ . This function should use the functions `conev` from your answer to part (a) and `rqd` from *spatial\_v2*. When calculating  $\dot{\mathbf{r}}$ , bear in mind that  $\dot{\mathbf{r}}$  is the velocity of the body-fixed point at  $\mathbf{r}$ , whereas the linear part of the spatial velocity is the velocity of the body-fixed point that coincides with the origin at the current instant. These two points are the same only when  $\mathbf{r} = \mathbf{0}$ , which happens only at  $t = 0$  and  $t = 1$ .
- Issue the Matlab command `[T,P]=ode45(@conepd,[0,1],p0);` where  $\mathbf{p}_0=[1;0;0;0;0;0;0]$  is the initial value of  $\mathbf{p}$ . This function will integrate the motion of the cone for one second. Plot the quaternion part of the result using `plot(T,P(:,1:4))` and the positional part of the result using `plot(T,P(:,5:7))`. Is the quaternion plot the same as in question 1? Do you understand the plot for  $\mathbf{r}$ ?
- Repeat part (c) using an initial value of  $\mathbf{p}_0=[1;0;0;0;0;0;1;0]$ . Can you explain the result?

### Question Sim3

Continuing with the cone in Figure 2, write a function `a=conea(t)` that calculates the spatial acceleration of the cone, and use the command `[T,V]=ode45(@(t,v)conea(t),[0,1],v0);` where  $\mathbf{v}_0=\text{conev}(0)$ , to integrate it to obtain the spatial velocity. (The expression `@(t,v)conea(t)` creates an anonymous function that takes two arguments,  $t$  and  $v$ , and calls `conea(t)`.) Compare the result with the velocity calculated directly by `conev`. Are they the same?

### Question Sim4

Using the functions in *spatial\_v2*, create a model of a spinning top and create a Simulink model demonstrating the precession of the spinning top under gravity. **Tips:** (1) the top will have to spin quickly in order to precess. If your top doesn't precess, then maybe you didn't give it a big enough initial velocity. (2) for easy compatibility with `showmotion`, save the joint position vector in 3D array format using a 'to workspace' Simulink block. (3) By default, Matlab saves

only the last 1000 time values in `tout`. If that is not enough then you can change it in the data import/export pane of the model configuration parameters window, which is accessed via the simulation menu.